

# **Robust multifunctionality!**

The new Leica DISTO<sup>™</sup> X310 is the only laser distance meter to be dust-tight and protected against water jets – to IP65. In addition, it passes drop tests of up to 2 m height. Thanks to the integrated tilt sensor, it can take indirect distance and height measurements absolutely precisely.

Leica DISTO<sup>TM</sup> X310 – guarantees reliable measurements, even under the harshest conditions.

# Featured with:

- IP65 water jet protection and dust-tight
- 360° tilt sensor
- Smart Horizontal Mode™
- Height tracking
- Power Range Technology™
- Illuminated 4-line display
- Automatic multifunctional end-piece



- when it has to be right



## **Robust housing**

The sensitive measuring elements are protected by solid rubber parts. Proven in drop tests from up to 2 m height, the Leica DISTO™ X310 is therefore particularly resistant.



#### **Protection class IP65**

The housing and keypad are specially sealed against water and dust. Cleaning under running water is also no problem.



#### Leica DISTO<sup>™</sup> X310 Art.No. 790656

Leica DISTO<sup>™</sup> X310 laser distance meter

Holster Hand loop

Batteries

#### **Technical Data** General



## Tilt sensor 360°

Thanks to the combination of distance and tilt measurements, you can determine the horizontal distance absolutely precisely and simply - even past obstructions. With the help of the tilt sensor, you can also determine indirect heights.



# Smart Horizontal Mode™

If obstructions prevent you from taking direct distance measurements, you can use the Smart Horizontal Mode<sup>™</sup> to determine the horizontal distance simply and absolutely precisely.

General	
Typical measuring accuracy	±1 mm
Range	80 m
Measuring units	0.000 m, 0.0000 m, 0.00 m, 0.00 ft, 0'00'' 1/32, 0.0 in, 0 in 1/32
Power Range Technology™	•
Distance in m Ø of the laser dot in mm	10, 50, 100 m 6, 30, 60 mm
Protection class	IP65 – water jet protection and dust-tight
Measurements per set of batteries	up to 5000
Batteries	Type AAA 2 x 1,5 V
Dimensions	122 x 55 x 31 mm
Weight with batteries	155 g
Functions	
Min/max measurement	•
Continuous measurement	•
Stake out function	•
Addition/subtraction	•
Area/volume	•
Painter function	•
Pythagoras	3 points, partial height
Smart Horizontal Mode	•
Height tracking	•
Memory	20 Displays
Illuminated display	•
Multifunctional	with automatic
end-piece	recognition



All illustrations, descriptions and technical specifications are subject to change without prior notice. Printed in Switzerland. Copyright Leica Geosystems AG, Heerbrugg, Switzerland, 2012.

Leica Geosystems AG Heerbrugg, Switzerland www.leica-geosystems.com

Dealer Stamp

SYNERGY POSITIONING SYSTEMS

3/52 Arrenway Drive, Albany Auckland, New Zealand Free Call: 0800-867-266 Fax: +64-9-476-5140 Website: www.synergypositioning.co.nz



Phone: +64-9-476-5151 Email: info@synergypositioning.co.nz



Laser Class 2 In accordance with IEC 60825-1



- when it has to be **right**