

Choke Ring Antenna



- Competitive high-end Geodetic Antenna
- Topcon's TA-5 vertical convex dipole antenna element for full spectrum GNSS signal tracking
- Topcon designed choke ring groundplane
- Environmentally robust and sealed
- Improved phase center stability in vertical over expanded GNSS frequency band. Improved low elevated satellites tracking.



Next Generation Full Wave Geodatic Antenna Anti-Snow Spherical Dome

The CR-G5 is a newly designed choke ring antenna based on Topcon’s new TA-5 full spectrum GNSS antenna element. The TA-5 antenna element utilizes an array of vertical convex dipoles. This new antenna provides Full Wave tracking technology for existing and future GNSS signals. The antenna addresses the evolving requirements for reference networks and infrastructure monitoring applications.

Topcon TotalCare

TotalCare provides a complete support and training solution for all of your positioning products, with online resources and real live people who are ready to help, and care about your productivity. Get expert training from Topcon University’s large collection of online training materials, including quick-guides and videos.

Receive expert help directly from Topcon’s Technical Support group. Access software and firmware updates, the latest Topcon publications, and exclusive access to the experts at Topcon... all right from your computer or your mobile device.

Please visit the TotalCare website to learn more. topcontotalcare.com



7400 National Drive • Livermore • CA 94550
(925) 245-8300

Specifications subject to change without notice. ©2012 Topcon Corporation All rights reserved. P/N: 7010-2087 Rev. B Printed in U.S.A. 4/12

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Topcon is under license. Other trademarks and trade names are those of their respective owners.

SPECIFICATIONS

Dimensions

Antenna without Anti-snow Dome	380 mm (D) x 155.5 mm (H)
With Topcon Anti-snow Spherical Dome	380 mm (D) x 292 mm (H)
With SCIGN Anti-snow Short Dome	415 mm (D) x 287 mm (H)

Weight

Antenna	4.9 kg
Topcon Anti-snow Spherical Dome	1.1 kg
Antenna w/ Topcon Anti-snow Spherical Dome	6 kg

Power

Input Voltage:	+3 to +12 VDC
Current Consumption:	100 mA (typical)
Connector:	N-type

Environmental

MIL-STD-810G	
Temperature	(Methods 501.5, 502.5)
Operating Range:	-50°C to +70°C
Storage Range:	-55°C to +85°C
Humidity	95%, Method 507.5
Salt Fog, 5%	Method 509.4
Vibration	Method 514.6, Broad band noise (random vibration), along each of 3 axes, Category 4, table 514.6C-IV
Mechanical Shock	Method 516.6, along each of 3 axes. Procedure I - Functional Shock, Table 516.6-I, Fig. 516.6-8, accelerative forces up to 40g
IP Rating	IEC 60529 IP67
Drop Test	Repeated drops from the height of 1 m on concrete surface. All sides – top, bottom & border (with Dome)
RoHS Compliant	Yes

Performance

Operating Frequency Range	
Lower band	1230 MHz±70 MHz (L5, E5B, E3, L2, G2, E4, E6)
Upper band	1565 MHz±50 MHz (E2, L1, E1, G1, OmniStar, SBAS, CDGPS)
Out-of-Band Rejection	
Upper band (1568.5 MHz ±150 MHz)	-40 dBc (typical)
Lower band (1232 MHz ± 100 MHz)	-60 dBc (typical)
Other bands	
f < 1000 MHz	-60 dBc (typical)
f > 1750 MHz	-60 dBc (typical)
LNA Gain	43 dB (typical)
Gain at Zenith (90°)	Lower band: +7.5 dB (typical) Upper band: +5 dB (typical)
Gain Roll-Off (from Zenith to Horizon)	Lower band: -16.5 dB (typical) Upper band: -13 dB (typical)
Noise Figure	1.0 dB (typical)
VSWR	1.5 : 1
Differential Propagation Delay (typical)	Lower band: 3 ns (maximum) Upper band: 3 ns (maximum)
Nominal Impedance	50 Ohm

Your local Authorized Topcon dealer is:

SYNERGY POSITIONING SYSTEMS
3/52 Arrenway Drive, Albany
Auckland, New Zealand

Free Call: 0800-867-266
Fax: +64-9-476-5140

Phone: +64-9-476-5151
Email: info@synergypositioning.co.nz

Website: www.synergypositioning.co.nz

